

V192

JSYV192D1-A2111

SEIKO WATCH CORPORATION

Copyright©2019 by SEIKO WATCH CORPORATION

Printed in Japan

D-13

SEIKO

V192

DIVER'S WATCH FOR AIR DIVING INSTRUCTIONS

日本語 **JA 1**

English **EN 1**

そのほかの言語の取扱説明書は、パソコンやスマートフォンから当社ホームページ内の「カスタマーサービス」>「取扱説明書ダウンロード」にアクセスいただき、ご覧ください。

Please refer to the Instruction Manuals of other languages by accessing "Customer Service"→ "Instruction" on our Website from PC or Smartphone.

Deutsch / Français / Italiano / Español /
Русский язык / العربية / Português /
简体中文 / 繁體中文 / 한국어 / ไทย



<https://www.seikowatches.com/>

**Thank you very much for choosing a SEIKO watch.
For proper and safe use of your SEIKO watch,
please read carefully the instructions in this
booklet before using it.**

Keep this manual handy for easy reference.

- * Length adjustment service for metallic bands is available at the retailer from whom the watch was purchased. If you cannot have your watch repaired by the retailer from whom the watch was purchased because you received the watch as a gift, or you moved to a distant place, please contact SEIKO CUSTOMER SERVICE CENTER. The service may also be available on a chargeable basis at other retailers, however, some retailers may not undertake the service.
- * If your watch has a protective film for preventing scratches, make sure to peel it off before using the watch. If the watch is used with the film on it, dirt, sweat, dust, or moisture may be attached to the film and may cause rust.

EN 1

⚠ WARNING

Make sure to read the following instructions before use and strictly observe them.

⚠ WARNING

When diving, never carry out operations other than those specified in this instruction manual. Mishandling of the product and misunderstanding of the displayed content may lead to a fatal or serious accident.

⚠ WARNING

The diver's watch is an auxiliary instrument which mainly displays the passage of time and does not ensure the safety of a user. Use this watch while using the equipment (residual pressure gauge, water depth meter, etc.) required for safe diving.

⚠ WARNING

Never use this watch for "saturation diving" using helium gas.

⚠ WARNING

Do not dive using this product unless you have been properly trained in scuba diving, acquired the requisite experience and techniques for safe diving, thoroughly familiarized yourself with the operation and handling of this product, and inspect all functions of this product prior to each dive.

⚠ CAUTION

Make sure to read the following instructions before use and strictly observe them.

⚠ CAUTION

Inspect the following items before diving (excluding saturation diving):

- The watch is normally operating.
- The remaining battery level is sufficient and the mainspring is sufficiently wound.
- The rotating bezel turns smoothly. (The bezel rotation must not be too loose or too tight.)
- Screws of the crown and other parts are reliably tightened.
- No abnormalities such as flaws or cracks exist on the band or glass.
- The band is reliably fixed (with spring bar, buckle or other parts.)

* If any abnormality is observed in the above items, do not use this watch for diving.

⚠ CAUTION

Do not operate the crown or buttons underwater.

⚠ CAUTION

As the use environment of the diver's watch may affect not only the case or band but also the internal mechanism of the watch, we recommend that you periodically request an overhaul for inspection and adjustment approximately once every three to four years.

EN 2

EN 3

CONTENTS

1 HOW TO USE

Handling cautions	6
Precautions for diving (Please make sure to observe the following.)	10
Before diving	10
While diving	12
After diving	13
Structure of the case	14
Characteristics	15
Names of the parts and their functions	16
Screw down crown	17
Screw lock type button	18
Toggling between displays	19
How to use the rotating bezel	20

2 HOW TO SET THE TIME AND DATE

How to set the time and date	22
How to set the time and date	22
Manual date adjustment at the end of the month	25

3 HOW TO USE THE STOPWATCH

Stopwatch function	26
The names of the parts and functions of the stopwatch	26
Before using the stopwatch	27
How to use the stopwatch	29

4 SOLAR CHARGING FUNCTION

Charging the battery	33
How to charge the battery	33
Guide to charging times	34
About energy	35
How to display the energy level	35

5 TO PRESERVE THE QUALITY OF YOUR WATCH

Daily care	36
Performance and type	37
Lumibrite	38
Power Source	39
Magnetic resistant performance	41
Band	43
How to use the diver adjuster	45
How to use the diver extender	47
After sales service	49

6 TROUBLESHOOTING

Setting the stopwatch hands (1/5-second and minute hands) to the preliminary position	51
Troubleshooting	55
If the hands fail to move or move abnormally even after recharging	58
Resetting the built-in IC	58

7 SPECIFICATIONS

Specifications	60
----------------------	----

Handling cautions

WARNING

Please note that there is a risk of serious consequences such as severe injury if the following safety regulations are not strictly observed.

Immediately stop wearing the watch in following cases:

- If the watch body or band becomes edged by corrosion etc.
 - If the pins protrude from the band.
- * Immediately consult the retailer from whom the watch was purchased or SEIKO CUSTOMER SERVICE CENTER.

Keep the watch and accessories out of the reach of babies and children.

Care should be taken to prevent a baby or a child accidentally swallowing the accessories. If a baby or child swallows the battery or accessories, immediately consult a doctor, as it will be harmful to the health of the baby or child.

Do not remove the secondary battery from the watch.

* About the secondary battery → Power Source → P. 39
Replacement of the secondary battery requires professional knowledge and skill. Please ask the retailer from whom the watch was purchased for replacement of the secondary battery.
Installation of an ordinary silver oxide battery can generate heat that can cause bursting and ignition.

CAUTION

Please note that there is a risk of minor injury or material damage if the following safety regulations are not strictly observed.

Avoid the following places for wearing or keeping the watch:

- Places where volatile agents (cosmetics such as polish remover, bug repellent, thinners etc.) are vaporizing
- Places where the temperature drops below 5°C or rises above 35°C for a long time
- Places affected by strong magnetism or static electricity
- Places affected by strong vibrations
- Places of high humidity
- Dusty places

If you observe any allergic symptoms or skin irritation

Stop wearing the watch immediately and consult a specialist such as a dermatologist or an allergist.

Other cautions

- For adjusting the length of the metallic band, specialized knowledge and expertise are necessary. Therefore, in such a case, contact the retailer from whom the watch was purchased. If you attempt to adjust the metallic band, injury may occur to your hand or fingers, or parts of the band may be lost.
- Do not disassemble or tamper with the watch.
- Keep the watch out of the reach of babies and children. Extra care should be taken to avoid risks of any injury or allergic rash or itching that may be caused when they touch the watch.
- If your watch is of the fob or pendant type, the strap or chain attached to the watch may damage your clothes, or injure the hand, neck, or other parts of your body.

⚠ WARNING

Never use the watch, in saturation diving using helium gas.

⚠ WARNING

While diving, never operate the watch in any other manner than set forth in the instruction manual.

⚠ WARNING

Before using the diver's watch, you have to be properly trained in various types of diving and possess the requisite experience and skill to dive safely. When diving, strictly abide by the rules of diving.

Precautions for diving (Please make sure to observe the following.)

■ Before diving

Before diving, check the following:

* "Names of the parts and their functions" → P. 16


1 The time is correctly set.

2 The energy level is at least "half full" and the small seconds hand is moving every second. If the small seconds hand is moving every two seconds or has stopped, expose the dial to light to charge the watch.

* "Charging the battery" → P. 33

3 The rotating bezel turns smoothly. (The bezel rotation must not be too loose or too tight.)

* "How to use the rotating bezel" → P. 20



⚠ CAUTION

Please note that there is a risk of minor injury or material damage if the following safety regulations are not strictly observed.



Do not turn or pull out the crown when the watch is wet.

Water may get inside of the watch.

* If the inner surface of the glass is clouded with condensation or water droplets appear inside of the watch for a long time, the water resistant performance of the watch is deteriorated. Immediately consult the retailer from whom the watch was purchased or SEIKO CUSTOMER SERVICE CENTER.



Do not leave moisture, sweat and dirt on the watch for a long time.

Be aware of a risk that a water resistant watch may lessen its water resistant performance because of deterioration of the adhesive on the glass or gasket.



Do not wear the watch while taking a bath or a sauna.

Steam, soap or some components of a hot spring may accelerate the deterioration of water resistant performance of the watch.


4 The crown and button screws are firmly tightened.

* "Screw down crown" → P. 17

* "Screw lock type button" → P. 18

5 There are no visible cracks or scratches on the crystal or watch band.

6 The band is firmly attached to the watch (with spring bars, clamp or other parts.)



⚠ CAUTION


If there are any malfunctions, contact the retailer from whom the watch was purchased or SEIKO CUSTOMER SERVICE CENTER.

■ While diving

Please observe the following cautions for use.



The watch can be used for air diving within the water resistant range displayed on the dial.



Do not operate the crown or buttons underwater.



Take care not to bump the watch against hard objects such as rocks.





Bezel rotation may become slightly harder in the water but this is not a malfunction.

■ Structure of the case

In the following types of models, take care of the following issues in usage.

The bezel or protective outer case is securely fastened to the watch with setscrews. Never loosen the setscrews.



* The above illustration is provided as an example, therefore it may not be exactly the same as your watch.

⚠ CAUTION

Never loosen the setscrews used to fix the bezel or protective outer case. Doing so may cause damage or result in further loosening.

* If you find that the setscrews have become loose or are functioning abnormally, consult the retailer from whom the watch was purchased or SEIKO CUSTOMER SERVICE CENTER.

■ After diving

Please follow the care instructions below after diving.



Rinse the watch in fresh water to wash out all seawater and wipe it thoroughly dry to prevent rust. Avoid pouring running water onto the watch directly from a faucet. Put some water into a bowl first, and then soak the watch in the water to wash it.

⚠ CAUTION

Depending on the environment where a diver's watch is used, its inner parts or movement as well as its case or band may be affected. We recommend that you have your watch overhauled regularly once every 3 or 4 years.

Characteristics

This solar watch is equipped with a stopwatch function.

- A full-scale stopwatch, which can measure in 1/5-second increments with the center hand, is equipped.
- A solar cell under the dial converts any form of light into "electrical energy" to operate the watch.
- * "Chronograph" means a watch with a stopwatch function.

■ Water resistant performance for air diving...

This watch is equipped with water resistant performance to be used in water for a long period of time with scuba diving tanks. (It cannot be used for saturation diving that uses helium gas.)

■ Stopwatch function.....

The stopwatch can measure up to 60 minutes in 1/5-second increments. After measuring 60 minutes, the stopwatch will automatically stop.

→ P. 26

■ Solar charging function.....

The watch charges by converting light that shines on the solar panel on the dial into electrical energy. After the battery is fully charged, the watch will operate for about six months even if the dial is not exposed to light.


→ P. 33

■ Energy level display function..

The energy level is displayed on the "charge level display".

→ P. 35

Names of the parts and their functions



- ① **Stopwatch 1/5-second hand (center hand)**
- ② **Hour hand**
- ③ **Small seconds hand**
- ④ **Stopwatch minute hand (energy level hand)**
- ⑤ **Rotating bezel**
- ⑥ **Minute hand**
- ⑦ **24-hour hand**
- ⑧ **Button A**
Toggling to the stopwatch display
- ⑨ **Crown**
 - Normal position (not locked): Stopwatch and charging functions
 - First click position: Date setting
 - Second click position: Setting the stopwatch hands to preliminary position, and performing a system reset
- ⑩ **Button B**
Toggling to the charge level display
- ⑪ **Date**

Screw down crown

The screw down crown features a mechanism that can securely lock the crown when it is not being operated in order to prevent any operational errors and to improve its water resistant performance.


- **It is necessary to unlock the screw down crown before operating it.**
- **Once you have finished operating the crown, make sure to relock it.**

[To unlock the crown]

Turn the crown counterclockwise to unscrew it. Now the crown can be operated.

[To lock the crown]

Turn the crown clockwise while gently pressing it in toward the watch body until it stops.



* When locking the crown, turn it slowly with care, ensuring that the screw is properly engaged. Be careful not to push it in forcefully, as doing so may damage the screw hole in the case.

Screw lock type button

The screw lock type button features a mechanism that can securely lock the button when it is not being operated in order to prevent any operational errors and to improve its water performance.


- **It is necessary to unlock the screw lock type button before operating it.**
- **Once you have finished operating the button, make sure to relock it.**

[To unlock the button]

- Turn the button ring counterclockwise until it stops.
- Now the button can be operated.

[To lock the button]

- Turn the button ring clockwise until it stops.
- Now the button can no longer be operated.




- * If the screw or button get dirty, they may not operate properly. "Daily care" → P. 36
- * Note that if you turn the button ring more than you need to, the screw lock button may be difficult to return to its original position.
- * Before you go diving, check that both buttons are properly locked.
- * Do not use the buttons when the watch is wet or when you are underwater.

Toggling between displays

The operation shown in the illustration below toggles between "charge level display" and "stopwatch display".

Toggling between the displays changes the function of the hands.



- * On the "charge level display", press button A to toggle to the "stopwatch display" and simultaneously start the stopwatch.
- * While the stopwatch is operating, you cannot toggle the display. To return to the "charge level display", first reset the stopwatch. During operation of the stopwatch, button B provides "split", "split reset" and "reset" functions. On resetting the stopwatch, the display automatically returns to "charge level display" after 1 minute.

How to use the rotating bezel


By setting the rotating bezel beforehand, the elapsed time since the start of an event can be measured.

- 1 At the start of the event, for which you want to measure the elapsed time (for example, when you start diving), rotate the bezel so that the ▼ mark on the bezel is aligned with the minute hand.**

* The rotating bezel is designed to rotate only counterclockwise.

Do not forcibly rotate it clockwise.
 ["One-Way rotating bezel"] → P. 21


Example: When you start diving at 10:10 am.



- 2 Read the graduation on the rotating bezel to which the minute hand is pointing.**

The graduation on the rotating bezel to which the minute hand is pointing indicates the elapsed time.

Example: After 20 minutes has elapsed



* The above illustration is provided as an example, therefore it may not be exactly the same as your watch.

[One-Way rotating bezel]

As the evaluation of the remaining air in your cylinder is based on the information of the elapsed time of the dive, the rotating bezel for a diver's watch is designed to rotate only counterclockwise, so that the watch is prevented from displaying the elapsed time shorter than it actually is.

CAUTION

Make sure that you check the correct remaining amount of air in your cylinder before diving. Use the display of the elapsed time by the rotating bezel only as a guide during diving.

How to set the time and date

How to set the time and date

* When setting the date only, refer to "Manual date adjustment at the end of the month" → P. 25.

- 1 Make sure that the watch is working.**

Check that the small seconds hand is moving every second.

If it is moving every two seconds or has stopped, expose the dial to light to charge the watch. "Charging the battery" → P. 33

- 2 Check that the watch hands are not displaying any time between 9 p.m. and 1 a.m.**

If a time between 9 p.m. and 1 a.m. is being displayed, pull the crown to the second click, advance the hands beyond the 1 a.m. position, and push the crown back in.


* This procedure is required to ensure the proper engagement of the date driving wheel.

* Each time the hour hand makes two full rotations, the date is adjusted by "one day". While turning the crown, the moment the date changes is midnight. Use the 24-hour hand to check whether the displayed time is a.m./p.m. "Names of the parts and their functions" → P. 16

- 3 Pull out the crown to the first click.**

The small seconds hand will continue to move.

* For models with screw down crown, please unlock the crown before operating it.



Pull out the crown to the first click

- 4 The date can be set by turning the crown.**

Turn it until the previous day's date appears.

Ex.) To display the date as "6," then set this to "5." Turn the crown to the right (clockwise) to set the date.


5 Pull out the crown to the second click and set the time.

Pull out when the small seconds hand has reached the 0 seconds position. (The small seconds hand will stop moving.)

Turn the crown to advance the hands until the date changes to the next. The time is now set for the A.M. period. Advance the hands to set the correct time.

* Use the 24-hour hand to check whether the displayed time is a.m./p.m.

* In order to set the time accurately, turn the minute hand 4 to 5 minutes ahead and then return it to the correct time.



6 Push the crown back in to the normal position in accordance with a time signal.

The small seconds hand will start moving.

* The telephone time signal service is helpful for setting the seconds hand exactly.


* For models with screw down crown, please be sure to lock the crown after operating it.

Stopwatch function

The stopwatch can measure up to 60 minutes in 1/5-second increments. After measuring 60 minutes, the stopwatch hands will automatically stop at the 0 minute 0 second position.

The names of the parts and functions of the stopwatch

Toggle to the "stopwatch display". "Toggling between displays" → P. 19



① **Center hand ⇒ stopwatch 1/5-second hand**

moves in 1/5-second increments

② **Button A**

Start/Stop

③ **Button B**

Split/Reset

④ **Energy level hand ⇒ stopwatch minute hand**

moves in one-minute increments

Manual date adjustment at the end of the month


It is necessary to adjust the date at the end of February and 30-day months.

Ex.) To adjust the date in the A.M. period on the first day of a month following a 30-day month

The watch displays "31" instead of "1." Pull out the crown to the first click.

Turn the crown clockwise to set the date to "1" and then push the crown back in to the normal position.

* For models with screw down crown, please be sure to lock the crown after operating it.



Pull out the crown to the first click

CAUTION

- Avoid amending the date when the watch is displaying between 9 PM and 1 AM. Doing so may cause damage.

Before using the stopwatch

The stopwatch on this watch can be started directly from the "charge level display".


On the stopwatch display, use the following operation to reset the stopwatch if it has not been reset. Do not use this operation otherwise.

Before using the stopwatch, reset it and check that the stopwatch hands (1/5-second hand, minute hand) are stopped at "0 seconds and 0 minutes". For how to reset the stopwatch, see the illustration below.

* The stopwatch will not operate when the small seconds hand is moving every 2 seconds. "About energy" → P. 35

How to reset the stopwatch

* The stopwatch can be operated when the crown is at the normal position.




If any of the stopwatch hands do not return to 0 minute 0 second when the stopwatch is reset, set the stopwatch hands to the preliminary hand position.

→ "Setting the stopwatch hands (1/5-second and minute hands) to the preliminary position" P. 51

3

HOW TO USE THE STOPWATCH




EN 28

How to use the stopwatch

* The stopwatch will not operate when the small seconds hand is moving every 2 seconds.
"About energy" → P. 35

• Standard measurement Ex. 5,000 meters running




3

HOW TO USE THE STOPWATCH

EN 29

• Accumulated elapsed time measurement Ex. Measuring the time for a soccer match




3

HOW TO USE THE STOPWATCH

EN 30

• Split time (intermediate elapsed time) measurement Ex. 5,000 meters running

* "Split time" is the time that has elapsed from the start of an activity to any given stage.




3

HOW TO USE THE STOPWATCH

EN 31




Measurement of two competitors



Charging the battery

How to charge the battery

Expose the dial to light to charge the watch.



To ensure optimal performance of the watch, make sure that the watch is kept sufficiently charged at all times.

Under the following situations, the energy of the watch is likely to be depleted, resulting in stoppage of the watch:

- The watch is concealed under a sleeve.
- The watch is used or stored under conditions where it cannot be exposed to light for a long time.

* Be careful to make sure that the watch does not get hot when it is charging. (The operating temperature range is -10°C to +60°C.)

* When you first start using the watch or starting it after it stopped due to a lack of charge, charge the watch sufficiently using the table on P. 34 as a guide.

Guide to charging times

Charge the watch using the times below as a guide.

Illuminance lx (LUX)	Light source	Condition (Example)	Time required for fully charging the watch	Time required to get the small seconds hand moving at one-second intervals	Time required for charging the watch to last for 1 day
700	Fluorescent light	General offices	-	60 hours	2.5 hours
3,000	Fluorescent light	30W 20cm	110 hours	13 hours	33 minutes
10,000	Fluorescent light	30W 5cm	30 hours	3.5 hours	9 minutes
10,000	Sunlight	Cloudy day	30 hours	3.5 hours	9 minutes
100,000	Sunlight	Sunny day (Under the direct sunlight on a summer day)	5 hours	36 minutes	2 minutes

The figures of "Time required for charging the watch to start moving at one-second intervals" are estimations of time required to charge the stopped watch by exposing it to light until it moves at steady one-second intervals. Even if the watch is partially charged for a shorter period, the watch will resume one-second-interval movement. However, it may shortly return to two-second-interval movement. Use the charging time in this column as a rough guide for sufficient charging time.

* The required charging time slightly varies depending on the model of the watch.

About energy

How to display the energy level

On the "charge level display", the energy level hand indicates the energy level. "Toggling between displays" → P. 19

Display			
Energy level	Full	Approximately half-full	Low
Approximate length of continuous operation	At least 100 days	2 days to 100 days	Less than 2 days
Solutions	Continue to use in current state	Use while paying attention to recharging	The small seconds hand will start "2-second movement" in which it moves every 2 seconds. Please charge until fully charged. * If the stopwatch is used, it will automatically reset and the display will change to the "charge level display".

* Please be aware that immediately after charging, the energy level display may show a level one higher than the actual level.

Daily care

● The watch requires good daily care

- Do not wash the watch when its crown is in the extended position.
- Wipe away moisture, sweat or dirt with a soft cloth.
- After soaking the watch in seawater, be sure to wash the watch in clean pure water and wipe it dry carefully.
Do not pour running water directly from a faucet onto the watch. Put some water into a bowl first, and then soak the watch in the water to wash it.
* If your watch is rated as “Non-water resistant” or “water resistant for everyday life”, do not wash the watch. “Performance and type” → P. 37

● Turn the crown from time to time


- In order to prevent corrosion of the crown, turn the crown from time to time.
- The same practice should be applied to a screw down crown.
“Screw down crown” → P. 17

● Press the buttons once in a while

- Press the buttons once in a while to prevent corrosion of the buttons
- The same applies to the screw-locked buttons.
“Screw lock type button” → P. 18

Performance and type

The case back shows the caliber and performance of your watch



- **Water resistant performance**
- **Case Number**
The number to identify the type of your watch.
- **Magnetic resistant performance**
Refer to pages P. 41 and P. 42.

* The above illustration is provided as an example, therefore it may not be exactly the same as your watch.

Lumibrite

If your watch has Lumibrite

Lumibrite is a luminous paint that absorbs the light energy of sunlight and lighting apparatuses in a short time and stores it to emit light in the dark. For example, if exposed to a light of more than 500 lux for approximately 10 minutes, Lumibrite can emit light for 3 to 5 hours. Please note, however, that, as Lumibrite emits the light it stores, the luminance level of the light decreases gradually over time. The duration of the emitted light may also differ slightly depending on such factors as the brightness of the place where the watch is exposed to light and the distance from the light source to the watch.

* In general, when coming from a place that is bright to a place that is dark, it takes human eyes some time to adapt to the darkness making it difficult to see objects initially. (Dark adaptation)

* Lumibrite is luminous paint that stores and emits light, which is harmless to human beings and the environment, containing no toxic materials such as radioactive substances.

<Brightness levels>

Condition		Illumination
Sunlight	Fine weather	100,000 lux
	Cloudy weather	10,000 lux
Indoor (Window-side during daytime)	Fine weather	more than 3,000 lux
	Cloudy weather	1,000 to 3,000 lux
	Rainy weather	less than 1,000 lux
Lighting apparatus (40-watt daylight fluorescent light)	Distance to the watch: 1 m	1,000 lux
	Distance to the watch: 3 m	500 lux (average room luminance)
	Distance to the watch: 4 m	250 lux

Power Source

The battery used in this watch is a special secondary battery, which is different from ordinary batteries.

Unlike an ordinary silver oxide battery, the secondary battery does not require periodic replacement.

The capacity or charging efficiency may gradually lower due to long-term use or operating environment.

In addition, long-term use may shorten the charge duration due to wear, contamination, lubricant deterioration of mechanical parts, etc. Request repair when the performance lowers.

⚠ WARNING

■ Notes on replacing the secondary battery

- Do not remove the secondary battery from the watch.
Replacement of the secondary battery requires professional knowledge and skill. Please ask the retailer from whom the watch was purchased for replacement of the secondary battery.
- Installation of an ordinary silver oxide battery can generate heat that can cause bursting and ignition.

* Overcharge prevention function

When the secondary battery is fully charged, the overcharge prevention function is automatically activated to avoid further charging.

There is no need to worry about damage caused by overcharging no matter how much the secondary battery is charged in excess of the "time required for fully charging the watch."

* For the required time to fully charge the battery, see "Guide to charging times" → P. 34.

⚠ WARNING

■ Notes on charging the watch

- When charging the watch, do not place the watch in close proximity to an intense light source such as lighting equipment for photography, spotlights or incandescent lights, as the watch may be excessively heated resulting in damage to its internal parts.
- When charging the watch by exposure to direct sunlight, avoid places that easily reach high temperatures, such as a car dashboard.
- Always keep the watch temperature under 60°C.

EN 40

Examples of common magnetic products that may affect watches



Smartphone, cellular phone,
tablet terminal (speaker)



AC adapter



Bag
(with magnet
buckle)



AC-powered
shaver




Magnetic cooking
device



Portable radio
(speaker)



Magnetic
necklace




Magnetic health
pillow

EN 42

Magnetic resistant performance

Affected by nearby magnetism,
a watch may temporarily gain or lose time or stop operating.

Diver's watches feature magnetic resistant performance which is equivalent to or above JIS Class 1.

⚠ DANGER	
Indication on the case back	Condition of use
No indication	Keep the watch more than 5 cm away from magnetic products. (JIS level-1 standard)
	Keep the watch more than 1 cm away from magnetic products. (JIS level-2 standard)

If the watch becomes magnetized and its accuracy deteriorates to an extent exceeding the specified rate under normal use, the watch needs to be demagnetized. In this case, you will be charged for demagnetization and accuracy readjustment even if it happens within the guarantee period.

The reason why a watch is affected by magnetism

The built-in motor is provided with a magnet, which may be influenced by a strong external magnetic field.

EN 41

Band

The band touches the skin directly and becomes dirty with sweat or dust. Therefore, lack of care may accelerate deterioration of the band or cause skin irritation or stain on the sleeve edge. The watch requires a lot of attention for long usage.

● Metallic band

- Moisture, sweat or soil will cause rust even on a stainless steel band if they are left for a long time.
- Lack of care may result in a rash or cause a yellowish or gold stain on the lower sleeve edge of shirts.
- Wipe off moisture, sweat or soil with a soft cloth as soon as possible.
- To clean the soil around the joint gaps of the band, wipe it out in water and then brush it off with a soft toothbrush.
(Protect the watch body from water splashes by wrapping it up in plastic wrap etc.)
Clean it off with a soft cloth.
- Because some titan bands use pins made of stainless steel, which has outstanding strength, rust may form in the stainless steel parts.
- If rust advances, pins may poke out or drop out, and the watch case may fall off the band, or the clasp may not open.
- If a pin is poking out, personal injury may result. In such a case, refrain from using the watch and request repair.

EN 43

● Polyurethane band

- A polyurethane band is susceptible to discoloration from light, and may be deteriorated by solvent or atmospheric humidity.
- Especially a translucent, white, or pale colored band easily adsorbs other colors, resulting in color smears or discoloration.
- Wash out dirt in water and clean it off with a dry cloth. (Protect the watch body from water splashes by wrapping it up in plastic wrap etc.)
- When the band becomes less flexible, have the band replaced with a new one. If you continue to use the band as it is, the band may develop cracks or become brittle over time.

● Silicone band


- As for material characteristics, the band is easily dirtied, and may be stained and discolored. Wipe off dirt with a wet cloth or cleaning tissue.
- Unlike bands of other materials, cracks may result in the band being cut. Take care not to damage the band with an edged tool.

Notes on skin irritation and allergy	Skin irritation caused by a band may result from various factors such as allergy to metals or leathers, or skin reactions against friction on dust or the band itself.
Notes on the length of the band	Adjust the band to allow a little clearance with your wrist to ensure proper airflow. When wearing the watch, leave enough room to insert a finger between the band and your wrist.




EN 44


- 3** While pressing the push button, lift up the clasp to release the buckle, and place the watch on your wrist.



- 4** Close the clasp (4-1) first and then, the flap (4-2).



- 5** Hold both sides of the band to adjust the length of the slider until it fits snugly around your wrist.



EN 46

How to use the diver adjuster

If your watch's metallic band has the Diver Adjuster function, the length of the band can be easily adjusted.


It is very useful when you wear the watch over a wet suit or winter clothing.

- 1** Lift up the flap approximately 90° until it stands upright, and then press the flap down further approximately 20° and lightly hold it.


- When doing so, take care not to push the flap forcibly. Although you may feel slight resistance, doing this requires only a light force.

- 2** Lightly pull the band on the 6 o'clock side of the watch along the curved line of the band to pull out the slider.

- Doing this requires only a light force. Take care not to pull the band forcibly.
- The slider can be pulled out approximately 30 mm. Take care not to pull it out more than this limit.



Band on the 6 o'clock side of the watch




EN 45

How to use the diver extender

If your watch's metallic band has the Diver Extender function, the length of the band can be easily adjusted.


It is very useful when you wear the watch over a wet suit or winter clothing.

- 1** Lift up the flap.



- 2** While pressing the push button, open the clasp.


- After opening the clasp, push the flap back to the normal position for safety's sake.



EN 47


3 Open the two-piece foldover portion of the Diver Extender in the direction of the arrow.

- Some force is required to open the foldover portion, and it will click when it is opened.




Two-piece foldover portion of the Diver Extender

4 Slide the upper cover of the Diver Extender in the direction of the arrow, and then, pull it up to extend the two-piece foldover portion to the full extent.



Upper cover of the Diver Extender

5 Place the watch on your wrist, and close the clasp (5-1) first and then, the flap (5-2).



Flap (5-2) Clasp (5-1)

- * To fold up the Diver Extender, reverse the procedure above. When the two-piece folder portion of the Diver Extender is folded up completely, it also clicks in the same manner as when it is opened.

EN 48

● Inspection and adjustment by disassembly and cleaning (overhaul)

- Periodic inspection and adjustment by disassembly and cleaning (overhaul) is recommended approximately once every 3 to 4 years in order to maintain optimal performance of the watch for a long time. According to use conditions, the oil retaining condition of your watch mechanical parts may deteriorate, abrasion of the parts may occur due to contamination of oil, which may ultimately lead the watch itself to stop. As the parts such as gasket may deteriorate, water-resistant performance may be impaired due to intrusion of perspiration and moisture. Please contact the retailer from whom the watch was purchased for inspection and adjustment by disassembly and cleaning (overhaul). For replacement of parts, please specify "SEIKO GENUINE PARTS." When asking for inspection and adjustment by disassembly and cleaning (overhaul), make sure that the gasket and push pin are also replaced with new ones.
- When your watch is inspected and adjusted by disassembly and cleaning (overhauled), the movement of your watch may be replaced.

⚠ CAUTION

Depending on the environment where a diver's watch is used, its inner parts or movement as well as its case or band may be affected. We recommend that you have your watch overhauled regularly once every 3 or 4 years.

EN 50

After sales service

● Notes on guarantee and repair

- Contact the retailer from whom the watch was purchased or SEIKO CUSTOMER SERVICE CENTER for repair or overhaul.
- Within the guarantee period, present the certificate of guarantee to receive repair services.
- Guarantee coverage is provided in the certificate of guarantee. Read carefully and retain it.
- For repair services after the guarantee period has expired, if the functions of the watch can be restored by repair work, we will undertake repair services upon request and payment.

● Replacement with functional parts

- Please keep in mind that if original parts are not available, they may be replaced with substitutes whose outward appearance may differ from the originals.

EN 49

Setting the stopwatch hands (1/5-second and minute hands) to the preliminary position

If any of the stopwatch hands do not return to the 0 minute 0 second position when the stopwatch is reset, the preliminary hand position may be misaligned.

Adjusting the hands to the preliminary position will ensure that stopwatch measurements are correct.

The preliminary position may be misaligned due to the following reasons.

- In the case of a strong impact: Misalignment may occur when dropping or hitting the watch.
 - In the case of a magnetic influence: Misalignment may occur when bringing the watch close to an object which generates magnetism.
- "Examples of common magnetic products that may affect watches" → P.42

- * If the preliminary position adjustment is carried out, the watch gains or loses time. After adjusting the preliminary hand position, make sure to reset the main time.


EN 51

1 Make sure that the watch is working.

Check that the small seconds hand is moving every second.
If it is moving every two seconds or has stopped, expose the dial to light to charge the watch. "Charging the battery" → P. 33

2 Pull out the crown to the second click.

The small seconds hand will stop moving.
* For models with screw down crown, please unlock the crown before operating it.




Pull out the crown to the second click.

3 Press and hold button A (for 3 seconds) until the stopwatch minute hand starts moving.

The stopwatch minute hand will move and the watch will enter "stopwatch minute hand" preliminary position alignment mode.

* If you do not know which hand is the stopwatch minute hand, refer to "Names of the parts and their functions" → P. 16.



Press and hold button A for 3 seconds


4 Press button B to set the stopwatch minute hand to the "34 minute position E".

One minute Advance	Press button B once and then release it.
Continuous Advance	When button B is kept pressed for two seconds or longer, the hand will start moving. When button B is released, the hand will stop.

* When the stopwatch minute hand is set to "34 minute position (E)", continue to procedure 5

5 Press and release button A

The stopwatch 1/5-second hand will move and the watch will enter "stopwatch 1/5-second hand" preliminary position alignment mode.




Press button B

Press and release button A

6 Press button B to set the stopwatch 1/5-second hand to "0 seconds".


1/5-second Advance	Press button B once and then release it.
Continuous Advance	When button B is kept pressed for two seconds or longer, the hand will start moving. When button B is released, the hand will stop.

* If the stopwatch 1/5-second hand is reset to 0 second, continue to procedure 7



Press button B

7 Push the crown back in to the normal position.



8 Set the main time.

"How to set the time and date" → P. 22
If the preliminary position adjustment is carried out, the main time may gain or lose time.
When the main time is set, the operation is completed.

Troubleshooting

Troubles	Possible causes	Solutions	Reference
The watch stops operating.	The power is completely depleted or low.	Keep charging until the small seconds hand is moving every second.	P. 33
The small seconds hand is moving every 2 seconds	If you wear the watch every day and this occurs, the most likely cause is the watch is hidden by your sleeves or other clothing when you wear it and it is not sufficiently exposed to light.	When you wear the watch, try to make sure that the watch is not hidden by your sleeves or other clothing. Additionally, when you take the watch off, try to place it in a bright place.	
The stopped watch was exposed to an adequate light for longer than "the time required to fully charge the watch," however, it does not resume its normal one-second interval movements or even does not start operating.	The internal watch system is unstable.	See "Resetting the built-in IC" → (P. 58) and follow the procedure.	P. 58
	The light is too weak. More time is required to fully charge the watch.	The time taken to charge will differ depending on the light intensity. For details on charging times, see "Guide to charging times" → (P. 34). If the hands still fail to resume operation, follow the procedure of "Resetting the built-in IC" → (P. 58).	P. 34 P. 58

Troubles	Possible causes	Solutions	Reference
The watch temporarily gains/loses time.	The watch has been left in extremely high or low temperatures for a long time.	If the watch returns to room temperature, the accuracy will return to its original state. If it does not return to its original state, contact the retailer from whom the watch was purchased.	-
	The watch has been left close to an object with a strong magnetic field.	Correct this condition by moving and keeping the watch away from the magnetic source, and reset the time. If this action does not correct the condition, contact the retailer from whom the watch was purchased.	-
	You drop the watch, hit it against a hard surface, or wear it while playing active sports. The watch is exposed to strong vibrations.	If accuracy does not return after setting the time, consult the retailer from whom the watch was purchased.	-
Any of the stopwatch hands do not return to the 0 minute 0 second position when the stopwatch is reset.	Any of the stopwatch hands are out of the preliminary position. This happens when the stopwatch hands are out of the preliminary position as a result of influence of various external sources or after the built-in IC is reset.	Adjust the preliminary position of stopwatch hands.	P. 51

If the hands fail to move or move abnormally even after recharging


When the watch shows an abnormal display or does not properly function, or does not move at all or at one-second intervals even after being fully charged, follow the instructions below to reset the built-in IC. Then the watch will resume its normal operation.

Resetting the built-in IC


1 Pull out the crown to the second click.

The small seconds hand will stop moving.

* For models with screw down crown, please unlock the crown before operating it.



2 Press and hold buttons A and B simultaneously for three seconds, and release.




Troubles	Possible causes	Solutions	Reference
The buttons do not work (Nothing happens when they are pressed)	The power is low.	Keep charging until the small seconds hand is moving every second.	P. 33
The date changes at 12 o'clock noon.	AM/PM is not properly set.	Advance the hands by 12 hours.	P. 22
Blur in the display persists.	Small amount of water has got inside the watch due to deterioration of the gasket, etc.	Consult the retailer from whom the watch was purchased.	-

* Contact the retailer from whom the watch was purchased for any other troubles.

3 Push the crown back in to the normal position.

The small seconds hand will start moving.

If the small seconds hand is moving every two seconds, keep charging until it is moving every second. → P. 33



4 Adjust the preliminary position of the stopwatch (1/5-second and minute) hands, and then set the time and date.

- [Adjusting the preliminary position of the stopwatch 1/5-second and minute hands](#) → P. 51.
- [How to set the time and date](#) → P. 22

When the preliminary position of the stopwatch hands (1/5-second and minute) are reset, and time and date are correctly set, the operation of resetting the built-in IC is completed.

Specifications

Cal.	V192
1.Features	3 hands for basic timekeeping (hour, minute and small seconds hand), 24-hour hand, date display, stopwatch hands (1/5-second and minute hand), charge level display.
2. Frequency of crystal oscillator	32,768 Hz (Hz = Vibrations per second)
3. Loss/gain (monthly rate)	Monthly average loss/gain \pm 15 seconds Only if worn on the wrist in a temperature range of 5°C to 35°C.
4. Operational temperature range	-10 °C ~ +60 °C
5. Driving system	Three step motors
6. Power source	Secondary battery, 1 piece
7. Duration	Approx. 6 months (if the stopwatch is used for 1 hour per day.)
8. IC (Integrated Circuit)	Oscillator, frequency divider and driving circuit C-MOSIC, 1 piece

* The specifications are subject to change without prior notice due to product improvements.